



T874C1000 THERMOSTAT
Q674A1001 SUBBASE

T87F/0539 OR 1F56
THERMOSTAT

24V
TERMINAL
BLOCK

YELLOW

CAPACITOR
5/370

OUTDOOR
MOTOR

BLACK

BROWN

T3 T2 T1
L3 L2 L1

TRANSFORMER
COMPRESSOR
CONTACTOR

208V

INDOOR
MOTOR

BLACK
BROWN

BLOWER
RELAY

CAPACITOR
5/370

6 PIN CONNECTOR FOR
OPTIONAL ELECTRIC
HEAT PACKAGE

EQUIP.
GROUND

TERMINAL
BLOCKS

LL3 LL2 LL1

FUSED
DISCONNECT
SWITCH

230/208V 60HZ 3-PH
220/200V 50HZ 3-PH

- ① REMOVE JUMPER FOR TWO STAGE HEAT
- ② NOT REQUIRED WHEN OPTIONAL HEAT PACKAGES ARE NOT INSTALLED
- ③ REQUIRED ONLY FOR USE WITH OPTIONAL ELECTRIC HEAT PACKAGES: EH3PA-A15, EH3PA-B12, EH3PA-B15, WHEN TWO STAGE HEAT IS DESIRED.
- ④ FOR 208V OPERATION MOVE THIS WIRE TO 208V TRANSFORMER TAP.

	FACTORY WIRING	FIELD WIRING
LOW VOLTAGE	_____	-----
HIGH VOLTAGE	_____	-----

USE COPPER OR
ALUMINUM WIRE