



USE COPPER CONDUCTORS ONLY  
SUITABLE FOR AT LEAST 75° C

230/208-60-1

COMPONENT CODE

CC	COMPRESSOR CONTACTOR	LAC	LOW AMBIENT CONTROL
COMP	COMPRESSOR	LPB	LOW PRESSURE BYPASS
DCC	DUAL CAN CAPACITOR	LPC	LOW PRESSURE CONTROL
DFC	DEFROST CONTROL	OFM	OUTDOOR FAN MOTOR
EHR	EMERGENCY HEAT RELAY	PL1	PLUG #1
GND	EQUIPMENT GROUND	RV	REV. VALVE SOLINOID
HPC	HIGH PRESSURE CONTROL	T	TRANSFORMER
IBC	INDOOR BLOWER CAPACITOR	TB	TERMINAL BLOCK
IBM	INDOOR BLOWER MOTOR	TBL	LOW VOLTAGE TERMINAL BLOCK
IBR	INDOOR BLOWER RELAY		
LAB	LOW AMBIENT BYPASS CONTROL		

<p><b>A</b>, <b>B</b> LABELED WIRES CONNECT IF NO OPTIONS USED. <b>A</b> MOVE RED WIRE TO 208V TAP FOR 208V OPERATION <b>A</b> RED (LOW) BLACK (HIGH) WHERE APPLICABLE</p>																																	
<p>HIGH VOLTAGE ——— FIELD - - - - - OPTIONAL - - - - -</p> <p>LOW VOLTAGE ——— FIELD - - - - - OPTIONAL - - - - -</p> <p>ACCESSORY ——— FIELD - - - - - OPTIONAL - - - - -</p>																																	
<p>COLOR CODE</p> <table border="1"> <tr> <td>BK</td> <td>BLACK</td> <td>Y</td> <td>YELLOW</td> <td>V</td> <td>VIOLET</td> <td>T</td> <td>TAN</td> </tr> <tr> <td>BR</td> <td>BROWN</td> <td>G</td> <td>GREEN</td> <td>(PR)</td> <td>PURPLE</td> <td>PK</td> <td>PINK</td> </tr> <tr> <td>R</td> <td>RED</td> <td>BL</td> <td>BLUE</td> <td>GY</td> <td>GRAY</td> <td>L</td> <td>LAVENDER</td> </tr> <tr> <td>O</td> <td>ORANGE</td> <td>W</td> <td>WHITE</td> <td>(S)</td> <td>SLATE</td> <td></td> <td></td> </tr> </table>		BK	BLACK	Y	YELLOW	V	VIOLET	T	TAN	BR	BROWN	G	GREEN	(PR)	PURPLE	PK	PINK	R	RED	BL	BLUE	GY	GRAY	L	LAVENDER	O	ORANGE	W	WHITE	(S)	SLATE		
BK	BLACK	Y	YELLOW	V	VIOLET	T	TAN																										
BR	BROWN	G	GREEN	(PR)	PURPLE	PK	PINK																										
R	RED	BL	BLUE	GY	GRAY	L	LAVENDER																										
O	ORANGE	W	WHITE	(S)	SLATE																												
<p><b>BARD MFG. CO.</b></p> <p>4066-116 A</p>																																	