



Model	Fan Capacitor
W48G*DC	15 / 370
W60G*DC	N/A

⚠️ COOLING BLOWER SPEED JUMPER. MOVE TO BLUE WIRE ON TERMINAL BLOCK
 ⚠️ IF BALANCED CLIMATE IS UTILIZED, THIS WIRE NEEDS TO BE CONNECTED
 IN CORRELATION WITH THE PURPLE WIRE ON THE TERMINAL BLOCK

IF ANY ORIGINAL WIRES SUPPLIED WITH THE APPLIANCE MUST BE REPLACED, IT MUST BE REPLACED WITH WIRING MATERIAL HAVING A TEMPERATURE RATING OF AT LEAST 105° C EXCEPT THE IGNITION CABLE WHICH IS 250° C HIGH VOLTAGE CABLE

⚠️ Same Letter Designated Wires Connect if Option Not Used

Wire Identification numbers for Bard use only. (99)
 2 RED - HIGH PRESSURE FAULT
 BLUE - LOW PRESSURE FAULT
 BLUE FLASH - LOW VOLTAGE

! DANGER
 ELECTRICAL SHOCK HAZARD
 DISCONNECT POWER BEFORE SERVICING.

! WARNING
 USE COPPER CONDUCTORS
 ONLY SUITABLE FOR AT LEAST 75° C.

	Factory	Field	Optional
High Voltage			
Low Voltage			