



Model	Fan Capacitor
W48G*DC	15 / 370
W60G*DC	N/A

IF ANY ORIGINAL WIRES SUPPLIED WITH THE APPLIANCE MUST BE REPLACED, IT MUST BE REPLACED WITH WIRING MATERIAL HAVING A TEMPERATURE RATING OF AT LEAST 105° C EXCEPT THE IGNITION CABLE WHICH IS 250° C HIGH VOLTAGE CABLE

- ⚠ COOLING BLOWER SPEED JUMPER. MOVE TO BLUE WIRE ON TERMINAL BLOCK
- ⚠ IF BALANCED CLIMATE IS UTILIZED, THIS WIRE NEEDS TO BE CONNECTED IN CORRELATION WITH THE PURPLE WIRE ON THE TERMINAL BLOCK

Same Letter Designated Wires Connect if Option Not Used

- Wire Identification numbers for Bard use only. (99)
- 2 RED - HIGH PRESSURE FAULT
 - 2 BLUE - LOW PRESSURE FAULT
 - 2 BLUE FLASH - LOW VOLTAGE

! DANGER
ELECTRICAL SHOCK HAZARD
DISCONNECT POWER BEFORE SERVICING.

! WARNING
USE COPPER CONDUCTORS
ONLY SUITABLE FOR AT LEAST 75° C.

	Factory	Field	Optional
High Voltage			
Low Voltage			

4085-396 A