



USE COPPER CONDUCTORS ONLY  
SUITABLE FOR AT LEAST 75° C

COMPONENT CODE

CB1	CIRCUIT BREAKER #1	LAB	LOW AMBIENT BYPASS CONTROL
CB2	CIRCUIT BREAKER #2	LAC	LOW AMBIENT CONTROL
CC	COMPRESSOR CONTACTOR	LPB	LOW PRESSURE BYPASS
CCH	COMPRESSOR CRANKCASE HEATER	LPC	LOW PRESSURE CONTROL
COMP	COMPRESSOR	LS	LIMIT SWITCH
CR1	CONTROL RELAY	ODT	OUTDOOR THERMOSTAT
DCC	DUAL CAN CAPACITOR	OPM	OUTDOOR FAN MOTOR
DFC	DEFROST CONTROL	PL1	PLUG #1
GND	EQUIPMENT GROUND	RV	REV. VALVE SOLINOID
H1	HEAT STRIP #1	SK	START KIT
H2	HEAT STRIP #2	SR	START RELAY
HCT	HEATER CONTACTOR #1	T	TRANSFORMER
HPC	HIGH PRESSURE CONTROL	TB	TERMINAL BLOCK
IBC	INDOOR BLOWER CAPACITOR	TBL	LOW VOLTAGE TERMINAL BLOCK
IBM	INDOOR BLOWER MOTOR	TCD	THERMAL CUTOFF
IBR	INDOOR BLOWER MOTOR		

△ Labeled wires connect if no options used. △ Move red wire to 208V tap for 208V operation. △ Black (high) red (low) if supplied.

FACTORY STD.	FIELD	OPTIONAL
HIGH VOLTAGE	---	---
LOW VOLTAGE	---	---
ACCESSORY	---	---

COLOR CODE

BK	BLACK	Y	YELLOW	V	VIOLET	T	TAN
BR	BROWN	G	GREEN	(PR)	PURPLE	PK	PINK
R	RED	BL	BLUE	GY	GRAY	L	LAVENDER
O	ORANGE	W	WHITE	(S)	SLATE		

BARD MFG. CO.

4096-112 B