



USE COPPER CONDUCTORS ONLY
SUITABLE FOR AT LEAST 75° C

COMPONENT CODE			
CB1	CIRCUIT BREAKER #1	HC2	HEATER CONTACTOR #2
CB2	CIRCUIT BREAKER #2	HPC	HIGH PRESSURE CONTROL
CC	COMPRESSOR CONTACTOR	IBC	INDOOR BLOWER CAPACITOR
CCH	COMPRESSOR CRANKCASE HEATER	IBR	INDOOR BLOWER RELAY
COMP	COMPRESSOR	LAB	LOW AMBIENT BYPASS CONTROL
DCC	DUAL CAN CAPACITOR	LAC	LOW AMBIENT CONTROL
DFC	DEFROST CONTROL	LPB	LOW PRESSURE BYPASS
EMR	EMERGENCY HEAT RELAY	LPC	LOW PRESSURE CONTROL
ERV	ENERGY RECOVERY VENTILATOR	LS	LIMIT SWITCH
FT	FREEZE T-STAT	OFM	OUTDOOR FAN MOTOR
GND	EQUIPMENT GROUND	PL1	PLUG #1
H1	HEAT STRIP #1	RAT	RETURN AIR THERMOSTAT
H2	HEAT STRIP #2		
HC1	HEATER CONTACTOR #1		
RLB	RELAY LOGIC BOARD		
RV	REV. VALVE SOLENOID		
SK	START KIT		
T	TRANSFORMER		
TB	TERMINAL BLOCK		
TBL	LOW VOLTAGE TERMINAL BLOCK		
TCD	THERMAL CUTOFF		
TWV	THREE WAY VALVE		

⚠️, ⚠️ Labeled wires connect if no options used. ⚠️ MOVE RED WIRE TO 208V TAP FOR 208V OPERATION ⚠️ RED (LOW) BLACK (HIGH) WHERE APPLICABLE

		COLOR CODE															
FACTORY STD.	FIELD	OPTIONAL	BK	BR	R	D	Y	G	BL	W	V	(PR)	GY	(S)	T	PK	L
HIGH VOLTAGE	---	---	BLACK	BROWN	RED	ORANGE	YELLOW	GREEN	BLUE	WHITE	VIOLET	PURPLE	GRAY	SLATE	TAN	PINK	LAVENDER
LOW VOLTAGE	---	---															
ACCESSORY	---	---															

BARD MFG. CO.
4096-231 C