



USE COPPER CONDUCTORS ONLY
SUITABLE FOR AT LEAST 75° C

A, **A** LABELED WIRES CONNECT IF NO OPTIONS USED.

A FOR LOW SPEED CONNECT BLACK AND ORANGE WIRES TOGETHER AND INSULATE. CONNECT RED WIRE TO TERMINAL 1 OF IBR

	FACTORY STD.	FIELD	OPTIONAL
HIGH VOLTAGE	————	-----	-----
LOW VOLTAGE	————	-----	-----
ACCESSORY	————	-----	-----

COLOR CODE					
BK	BLACK	Y	YELLOW	V	VIOLET
BR	BROWN	G	GREEN	(PR)	PURPLE
R	RED	BL	BLUE	GY	GRAY
O	ORANGE	W	WHITE	(S)	SLATE
				T	TAN
				PK	PINK
				L	LAVENDER

BARD MFG. CO.
4096-314 C

COMPONENT CODE

CC	COMPRESSOR CONTACTOR	LBP	LOW PRESSURE BYPASS
CCH	COMPRESSOR CRANKCASE HEATER	LPC	LOW PRESSURE CONTROL
COMP	COMPRESSOR	LS	LIMIT SWITCH
DCC	DUAL CAN CAPACITOR	LS	LIMIT SWITCH
DFC	DEFROST CONTROL	ODT	OUTDOOR THERMOSTAT
EHR	EMERGENCY HEAT RELAY	OFM	OUTDOOR FAN MOTOR
GND	GROUND	OFR	OUTDOOR FAN RELAY
H1	HEAT STRIP #1	PL1	PLUG #1
H2	HEAT STRIP #2	PD	PULL DISCONNECT
HC1	HEATER CONTACTOR #1	RV	REV. VALVE SOL.INOTD
HC2	HEATER CONTACTOR #2	SR	STAGING RELAY
HPC	HIGH PRESSURE CONTROL	SK	START KIT
IBC	INDOOR BLOWER CAPACITOR	T	TRANSFORMER
IBM	INDOOR BLOWER MOTOR	TB	TERMINAL BLOCK
IBR	INDOOR BLOWER RELAY	TBL	LOW VOLTAGE TERMINAL BLOCK
		TCO	THERMAL CUTOFF