



COMPONENT CODE			
CB1	CIRCUIT BREAKER #1	LPB	LOW PRESSURE BYPASS
CB2	CIRCUIT BREAKER #2	LPC	LOW PRESSURE CONTROL
CC	COMPRESSOR CONTACTOR	LS	LIMIT SWITCH
COMP	COMPRESSOR	MSR	MOTOR SPEED RELAY
DFC	DEFROST CONTROL	DFC	OUTDOOR FAN CAPACITOR
EHR	EMERGENCY HEAT RELAY	DFM	OUTDOOR FAN MOTOR
GND	EQUIPMENT GROUND	DFR	OUTDOOR FAN RELAY
H1	HEAT STRIP #1	DMT	OUTDOOR MOTOR THERMOSTAT
HC1	HEATER CONTACTOR #1	PL1	PLUG #1
HPC	HIGH PRESSURE CONTROL	PM	PHASE MONITOR
IBC	INDOOR BLOWER CAPACITOR	RV	REV. VALVE SOLINOID
IBM	INDOOR BLOWER MOTOR	T	TRANSFORMER
IBR	INDOOR BLOWER RELAY	TB, TB2	TERMINAL BLOCK
LAB	LOW AMBIENT BYPASS	TBL	LOW VOLTAGE TERMINAL BLOCK
LAC	LOW AMBIENT CONTROL	TCO	THERMAL CUTOFF

USE COPPER CONDUCTORS ONLY
SUITABLE FOR AT LEAST 75° C

⚠️ ⚠️ ⚠️ LABELED WIRES CONNECT IF NO OPTIONS USED. ⚠️ FOR LOW & MEDIUM SPEEDS CONNECT ORANGE TO BLACK. RED (LOW) OR BLUE (MEDIUM) TO T1 OF IBR. FOR HIGH SPEED TAPE ORANGE, RED, BLUE LEADS SEPARATELY. CONNECT BLACK TO T1 OF IBR.

	FACTORY STD.	FIELD	OPTIONAL
HIGH VOLTAGE	————	- - - -	- - - -
LOW VOLTAGE	————	- - - -	- - - -
ACCESSORY	————	- - - -	- - - -

COLOR CODE					
BK	BLACK	Y	YELLOW	V	VIOLET
BR	BROWN	G	GREEN	(PR)	PURPLE
R	RED	BL	BLUE	GY	GRAY
O	ORANGE	W	WHITE	(S)	SLATE
		T	TAN	PK	PINK
		L	LAVENDER		

BARD MFG. CO.
4096-318 B