



COMPONENT CODE			
CC	COMPRESSOR CONTACTOR	LAC	LOW AMBIENT CONTROL
CCH	COMPRESSOR CRANKCASE HEATER	LBP	LOW PRESSURE BYPASS
COMP	COMPRESSOR	LPC	LOW PRESSURE CONTROL
DFC	DEFROST CONTROL	LS	LIMIT SWITCH
EHR	EMERGENCY HEAT RELAY	DFC	OUTDOOR FAN CAPACITOR
GND	GROUND	OFM	OUTDOOR FAN MOTOR
H1	HEAT STRIP #1	DFR	OUTDOOR FAN RELAY
H2	HEAT STRIP #2	PL1	PLUG #1
HC1	HEATER CONTACTOR #1	PD	PULL DISCONNECT
HC2	HEATER CONTACTOR #2	PM	PHASE MONITOR
HPC	HIGH PRESSURE CONTROL	RV	REV. VALVE SOLINOID
IBC	INDOOR BLOWER CAPACITOR	SK	START KIT
IBM	INDOOR BLOWER MOTOR	T	TRANSFORMER
IBR	INDOOR BLOWER RELAY	TB	TERMINAL BLOCK
LAB	LOW AMBIENT BYPASS	TBL	LOW VOLTAGE TERMINAL BLOCK
		TCO	THERMAL CUTOFF

USE COPPER CONDUCTORS ONLY
SUITABLE FOR AT LEAST 75° C

⚠ , **⚠** LABELED WIRES CONNECT IF NO OPTIONS USED. **⚠** FOR LOW & MEDIUM SPEEDS CONNECT ORANGE TO BLACK. RED (LOW) OR BLUE (MEDIUM) TO T1 OF IBR. FOR HIGH SPEED TAPE ORANGE, RED, BLUE LEADS SEPARATELY. CONNECT BLACK TO T1 OF IBR.

HIGH VOLTAGE LOW VOLTAGE ACCESSORY	FACTORY STD.			FIELD			OPTIONAL			COLOR CODE			BARD MFG. CO. 4096-327 B		
	---	---	---	---	---	---	---	---	---	---	---	---			
BK	BLACK	Y	YELLOW	V	VIOLET	T	TAN	BK	BLACK	Y	YELLOW	V	VIOLET	T	TAN
BR	BROWN	G	GREEN	(PR)	PURPLE	PK	PINK	BR	BROWN	G	GREEN	(PR)	PURPLE	PK	PINK
R	RED	BL	BLUE	GY	GRAY	L	LAVENDER	R	RED	BL	BLUE	GY	GRAY	L	LAVENDER
O	ORANGE	W	WHITE	(S)	SLATE			O	ORANGE	W	WHITE	(S)	SLATE		