

1 BLUE (MED.), BLACK (HIGH) WHERE APPLICABLE

USE COPPER CONDUCTORS ONLY SUITABLE FOR AT LEAST 75° C

USE CLASS 1 WIRING FOR ALL CONNECTIONS TO THE LOW VOLTAGE TERMINAL BLOCK

COMPONENT CODE

ALR	ALARM RELAY	IBC	INDOOR BLOWER CAPACITOR	T	TRANSFORMER
COMP	COMPRESSOR	IBR	INDOOR BLOWER RELAY	TB	TERMINAL BLOCK
CB	CIRCUIT BREAKER	LAC	LOW AMBIENT CONTROL	TBL	LOW VOLT TERM BLOCK
CC	COMPRESSOR CONTACTOR	LPC	LOW PRESSURE CONTROL	TCO	THERMAL CUTOFF
CCM	COMPRESSOR CONTROL MODULE	LS	LIMIT SWITCH	TDR	TIME DELAY RELAY
DCC	DUAL CAN CAPACITOR	ODT	OUTDOOR THERMOSTAT		
GND	GROUND	OFM	OUTDOOR FAN MOTOR		
H1	HEAT STRIP	PL1	PLUG, 9 PIN		
HPC	HIGH PRESSURE CONTROL	PL2	PLUG, 2 PIN		

COLOR CODE

BK	BLACK	G	GREEN
BR	BROWN	BL	BLUE
R	RED	PR	PURPLE
O	ORANGE	GY	GRAY
Y	YELLOW	PK	PINK

	HIGH VOLTAGE	LOW VOLTAGE	ACCESSORY
FACTORY STD.	———		- - -
FIELD	- - -	- - -	
OPTIONAL	———		

ALARM RELAY CONTACT RATINGS 125VA @ 24VAC

4104-100 C