



▲ BLUE (MED.), BLACK (HIGH) WHERE APPLICABLE

USE COPPER CONDUCTORS ONLY SUITABLE FOR AT LEAST 75° C

USE CLASS 1 WIRING FOR ALL CONNECTIONS TO THE LOW VOLTAGE TERMINAL BLOCK

COMPONENT CODE			
ALR	ALARM RELAY	PL1	PLUG, 9 PIN
COMP	COMPRESSOR	PL2	PLUG, 2 PIN
CB	CIRCUIT BREAKER	T	TRANSFORMER
CC	COMPRESSOR CONTACTOR	TB	TERMINAL BLOCK
CCH	CRANKCASE HEATER	TBL	LOW VOLT TERM BLOCK
CCM	COMPRESSOR CONTROL MODULE	TCO	THERMAL CUTOFF
GND	GROUND	TDR	TIME DELAY RELAY
H1	HEAT STRIP		
HPC	HIGH PRESSURE CONTROL		
IBC	INDOOR BLOWER CAPACITOR		
IBM	INDOOR BLOWER MOTOR		
IBR	INDOOR BLOWER RELAY		
LAC	LOW AMBIENT CONTROL		
LPC	LOW PRESSURE CONTROL		
LS	LIMIT SWITCH		
ODT	OUTDOOR THERMOSTAT		
OFM	OUTDOOR FAN MOTOR		

COLOR CODE			
BK	BLACK	G	GREEN
BR	BROWN	BL	BLUE
R	RED	PR	PURPLE
O	ORANGE	GY	GRAY
Y	YELLOW	PK	PINK

	HIGH VOLTAGE	LOW VOLTAGE	ACCESSORY
FACTORY	---	---	---
STD.	---	---	---
FIELD	---	---	---
OPTIONAL	---	---	---

ALARM RELAY CONTACT RATINGS
125VA @ 24VAC

4104-201 A