



RED (LOW), BLACK (HIGH)
WHERE APPLICABLE

USE COPPER CONDUCTORS
ONLY SUITABLE FOR AT
LEAST 75° C

USE CLASS 1 WIRING
FOR ALL CONNECTIONS
TO THE LOW VOLTAGE
TERMINAL BLOCK

COMPONENT CODE

| | | | | | |
|------|---------------------------|-----|-------------------------|-----|---------------------|
| ALR | ALARM RELAY | IBC | INDOOR BLOWER CAPACITOR | PL1 | PLUG, 9 PIN |
| COMP | COMPRESSOR | IBM | INDOOR BLOWER MOTOR | PL2 | PLUG, 2 PIN |
| CB | CIRCUIT BREAKER | IBR | INDOOR BLOWER RELAY | T | TRANSFORMER |
| CC | COMPRESSOR CONTACTOR | LAC | LOW AMBIENT CONTROL | TB | TERMINAL BLOCK |
| CCH | CRANKCASE HEATER | LPC | LOW PRESSURE CONTROL | TBL | LOW VOLT TERM BLOCK |
| CCM | COMPRESSOR CONTROL MODULE | LS | LIMIT SWITCH | TCD | THERMAL CUTOFF |
| GND | GROUND | ODT | OUTDOOR THERMOSTAT | TDR | TIME DELAY RELAY |
| H1 | HEAT STRIP | OFM | OUTDOOR FAN MOTOR | | |
| HPC | HIGH PRESSURE CONTROL | | | | |

COLOR CODE

| | | | |
|----|--------|----|--------|
| BK | BLACK | G | GREEN |
| BR | BROWN | BL | BLUE |
| R | RED | PR | PURPLE |
| O | ORANGE | GY | GRAY |
| Y | YELLOW | PK | PINK |

| | HIGH VOLTAGE | LOW VOLTAGE | ACCESSORY |
|--------------|--------------|-------------|-----------|
| FACTORY STD. | --- | --- | --- |
| FIELD | --- | --- | --- |
| OPTIONAL | --- | --- | --- |

ALARM RELAY CONTACT RATINGS
125VA @ 24VAC

4104-201 B