



COMPONENT CODE

ALR	ALARM RELAY	IBC	INDOOR BLOWER CAPACITOR	PL1	PLUG, 9 PIN
COMP	COMPRESSOR	IBM	INDOOR BLOWER MOTOR	PL2	PLUG, 2 PIN
CB	CIRCUIT BREAKER	IBR	INDOOR BLOWER RELAY	T	TRANSFORMER
CC	COMPRESSOR CONTACTOR	LAC	LOW AMBIENT CONTROL	TB	TERMINAL BLOCK
CCH	CRANKCASE HEATER	LPC	LOW PRESSURE CONTROL	TBL	LOW VOLT TERM BLOCK
CCM	COMPRESSOR CONTROL MODULE	LS	LIMIT SWITCH	TCD	THERMAL CUTOFF
GND	GROUND	ODT	OUTDOOR THERMOSTAT	TDR	TIME DELAY RELAY
H1	HEAT STRIP	DFM	OUTDOOR FAN MOTOR		
HPC	HIGH PRESSURE CONTROL				

RED (LOW), BLACK (HIGH) WHERE APPLICABLE

USE COPPER CONDUCTORS ONLY SUITABLE FOR AT LEAST 75° C

USE CLASS 1 WIRING FOR ALL CONNECTIONS TO THE LOW VOLTAGE TERMINAL BLOCK

COLOR CODE

BK	BLACK	BL	BLUE
BR	BROWN	PR	PURPLE
R	RED	GY	GRAY
O	ORANGE	PK	PINK
Y	YELLOW		

	HIGH VOLTAGE	LOW VOLTAGE	ACCESSORY
FACTORY STD.	---	---	---
FIELD	---	---	---
OPTIONAL	---	---	---

ALARM RELAY CONTACT RATINGS
125VA @ 24VAC

4104-211 B