460-60-3

L1 L2 L3

PL1 — 6 Pin Electric Heat Plug

Blower Speeds

Red - Low
Blue - Med
Black - High

Evaporator Section — 13 Blower Speed Plug (1 2 3 4 5) — 12 Blower Power Plug (C L1 G N)

Blower Relay 150

Alarm Relay 23

Analog Ground Terminal 26

Digital Ground Terminal 26

Mixed Air Sensor 97

Outdoor temp and humidity sensor

Electonic Exp. Valve — EEV 129

Dirty Filter Switch 30

Low Pressure Switch

Evap. Temp. Sensor 37

Treminal Block 7

TRANSFORMER 17

35 Programmable Logic Control

Phase Monitor 136

Suction Pressure — SP 126

Suction Temperature — ST 124

DEHUM VALVE

Auxiliary NC Contact 140

Compressor Contactor 14

Low Ambient Control (opt.)

Compressor

COMPRESSOR CRANK CASE HEATER

COMPRESSOR CONTROL MODULE — CC ALR C MINUTES HPC R Y LPC

HP 103

Outdoor Fan Capacitor 2

Red (50 hz only)(Low), Black (High) where applicable

Outdoor Fan Motor

10 Terminal

Damper Actuator Motor (OPT.) — 2....10 Vdc, 2....10 Vdc, 24 Vac/Vdc — 2 | Com | 1 | 3 | 5 | + | Y | U

VENT PLUG

DBS/RAS PLUG

Female Side

Male Side

Damper Blade Switch (OPT.) — NO NC

Return Air Sensor

	Factory	Field	Optional
High Voltage	———	- - - -	— - —
Low Voltage	———	- - - -	— - —
D-10VDC	— - —		

4207-306 B