



DAMPER MOTOR					
Belimo			Honeywell Motor		
Wire Color	Terminal Number	Symbol	Wire Color	Terminal Number	Symbol
BK/W	1	-	BK/W	2	GND
R/W	2	+	R/W	1	24 VAC
BR/W	3	Y	BR/W	3	2-10 VDC

- | | | | | | | | |
|------|---------------------------------|-----|-----------------------------|-----|---------------------|-----|------------------------------|
| LT | LIQUID TEMPERATURE | SP | SUCTION PRESSURE TRANSDUCER | ST | SUCTION TEMPERATURE | HPS | HIGH PRESSURE SWITCH |
| AFS | AIR FLOW SWITCH | LP | LIQUID PRESSURE TRANSDUCER | BS | BLADE SWITCH | CCH | CRANK CASE HEATER |
| DFS | DIRTY FILTER SWITCH | SAT | SUPPLY AIR TEMPERATURE | DFL | DIRTY FILTER LITCH | EEV | ELECTRONIC EXPANSION VALVE |
| OATH | OUTDOOR TEMP. AND HUMID. SENSOR | RAT | RETURN AIR TEMPERATURE | TB | OTERMINAL BLOCK | RDS | REFRIGERANT DETECTION SYSTEM |

	Factory	Field	Optional
High Voltage		---	---
Low Voltage		---	---
D-10VDC	---		